

WHAT IS CLAIMED IS:

1. A solid-state crossbar switch for transmitting data traffic, comprising:

5 a first number of input ports, each input port operable to receive DSL data from a data switch;

a second number of output ports, each output port capable of being coupled to a customer premise equipment (CPE) device; and

10 a third number of 1 x N solid-state analog switches, each 1 x N solid-state analog switch operable to couple one of the input ports with N output ports.

15 2. The crossbar switch of Claim 1, wherein each input port is coupled to one of the 1 x N solid-state analog switches.

3. The crossbar switch of Claim 1, wherein the second number of output ports is greater than N.

20 4. The crossbar switch of Claim 1, further comprising a sweeper port coupled to each output port, wherein the sweeper port is operable to monitor each output port to detect an active connection of a CPE device to one of the output ports.

25

5. The crossbar switch of Claim 4, wherein the first number is twenty-three.

10

15

20

25

30

11. The crossbar switch of Claim 1, wherein the second number is ninety-six.

12. The crossbar switch of Claim 1, wherein N is approximately between twelve and thirty-two.

14. The crossbar switch of Claim 1, wherein N is  
5 twenty-four.

15. A solid-state crossbar switch for transmitting data traffic, comprising:

a first number of input ports, each input port operable to receive DSL data from a data switch;

5 a second number of output ports, each output port capable of being coupled to a customer premise equipment (CPE) device;

a first number of solid-state analog switches, each solid-state analog switch operable to couple one of the  
10 input ports with each output port; and

a sweeper port coupled to each output port, wherein the sweeper port is operable to monitor each output port to detect an active connection of a CPE device to one of the output ports.

15

16. The crossbar switch of Claim 15, wherein the first number is twenty-three.

17. The crossbar switch of Claim 15, wherein the  
20 second number is ninety-six.

100-443-4330

18. A method for transmitting DSL data between a data switch and a CPE device using a solid-state crossbar switch, comprising:

receiving DSL data from the data switch at a first  
5 number of input ports;

receiving the DSL data from the input ports at a second number of  $1 \times N$  solid-state analog switches, wherein each  $1 \times N$  solid-state analog switch comprises  $N$  outlets;

10 switching the DSL data received at each analog switch to an outlet of each analog switch; and

receiving the switched DSL data at a third number of output ports, each output port capable of being coupled to a CPE device.

15

19. The method of Claim 18, wherein each input port is coupled to one of the analog switches.

20. The method of Claim 18, wherein the third  
20 number of output ports is greater than  $N$ .

21. The method of Claim 18, wherein the first number is twenty-four.

22. The method of Claim 18, wherein the third  
25 number is ninety-six.

23. The method of Claim 18, wherein  $N$  is approximately between twelve and thirty-two.

30

24. The method of Claim 18, further comprising  
monitoring each output port to detect an active  
connection of a CPE device to one of the output ports  
using a sweeper port, wherein the sweeper port is coupled  
5 to each output port.

25. The method of Claim 24, wherein the first  
number is twenty-three.

10 26. The method of Claim 24, further comprising  
monitoring each output port to detect an active  
connection of a CPE device to one of the output ports and  
forming an active connection with one of the output ports  
to alleviate a bad cluster using a catcher port, wherein  
15 the catcher port is coupled to each output port.

27. The method of Claim 24, wherein the first  
number is twenty-two.

20 28. The method of Claim 18, further comprising  
monitoring each output port to detect an active  
connection of a CPE device to one of the output ports and  
forming an active connection with one of the output ports  
to alleviate a bad cluster using a catcher port, wherein  
25 the catcher port is coupled to each output port.

29. The method of Claim 28, wherein the first  
number is twenty-three.

30. An apparatus for transmitting DSL data between a data switch and a CPE device using a solid-state crossbar switch, comprising:

means for receiving DSL data from the data switch at  
5 a first number of input ports;

means for receiving the DSL data from the input ports at a second number of  $1 \times N$  solid-state analog switches, wherein each  $1 \times N$  solid-state analog switch comprises  $N$  outlets;

10 means for switching the DSL data received at each analog switch to an outlet of each analog switch; and

means for receiving the switched DSL data at a third number of output ports, each output port capable of being coupled to a CPE device.

15

31. The apparatus of Claim 30, further comprising means for monitoring each output port to detect an active connection of a CPE device to one of the output ports using a sweeper port, wherein the sweeper port is coupled  
20 to each output port.

32. The apparatus of Claim 30, further comprising means for monitoring each output port to detect an active connection of a CPE device to one of the output ports and  
25 means for forming an active connection with one of the output ports to alleviate a bad cluster using a catcher port, wherein the catcher port is coupled to each output port.

33. Logic encoded in media for transmitting DSL data between a data switch and a CPE device using a solid-state crossbar switch, the logic operable to perform the following steps:

5       receive DSL data from the data switch at a first number of input ports;

          receive the DSL data from the input ports at a second number of  $1 \times N$  solid-state analog switches, wherein each  $1 \times N$  solid-state analog switch comprises  $N$   
10       outlets;

          switch the DSL data received at each analog switch to an outlet of each analog switch; and

          receive the switched DSL data at a third number of output ports, each output port capable of being coupled  
15       to a CPE device.

34. The logic encoded in media of Claim 33, wherein the logic is further operable to monitor each output port to detect an active connection of a CPE device to one of  
20       the output ports using a sweeper port, wherein the sweeper port is coupled to each output port.

35. The logic encoded in media of Claim 33, wherein the logic is further operable to monitor each output port to detect an active connection of a CPE device to one of  
25       the output ports and form an active connection with one of the output ports to alleviate a bad cluster using a catcher port, wherein the catcher port is coupled to each output port.



36. A crossbar switch for transmitting data traffic, comprising:

a first number of input ports, each input port operable to receive data from a data switch;

5 a second number of output ports, each output port capable of being coupled to a customer premise equipment (CPE) device; and

a third number of  $1 \times N$  analog switches, each  $1 \times N$  analog switch operable to couple one of the input ports  
10 with  $N$  output ports, wherein  $N$  is less than the second number.

37. The crossbar switch of Claim 36, wherein the first number is twenty-four.

15 38. The crossbar switch of Claim 36, wherein the second number is ninety-six.

20 39. The crossbar switch of Claim 36, wherein  $N$  is sixteen.

40. A method for transmitting data between a data switch and a CPE device using a crossbar switch, comprising:

5 receiving data from the data switch at a first number of input ports;

receiving the data from the input ports at a second number of  $1 \times N$  analog switches, wherein each  $1 \times N$  analog switch comprises  $N$  outlets;

10 switching the data received at each analog switch to an outlet of each analog switch; and

receiving the switched data at a third number of output ports, each output port capable of being coupled to a CPE device, wherein the third number is greater than  $N$ .

15

41. The method of Claim 40, wherein the first number is twenty-four.

20 42. The method of Claim 40, wherein the third number is ninety-six.

43. The method of Claim 40, wherein  $N$  is sixteen.

44. An apparatus for transmitting data between a data switch and a CPE device using a crossbar switch, comprising:

means for receiving data from the data switch at a  
5 first number of input ports;

means for receiving the data from the input ports at a second number of  $1 \times N$  analog switches, wherein each  $1 \times N$  analog switch comprises  $N$  outlets;

means for switching the data received at each analog  
10 switch to an outlet of each analog switch; and

means for receiving the switched data at a third number of output ports, each output port capable of being coupled to a CPE device, wherein the third number is greater than  $N$ .

40301

45. Logic encoded in media for transmitting data between a data switch and a CPE device using a crossbar switch, the logic operable to perform the following steps:

5       receive data from the data switch at a first number of input ports;

          receive the data from the input ports at a second number of  $1 \times N$  analog switches, wherein each  $1 \times N$  analog switch comprises  $N$  outlets;

10       switch the data received at each analog switch to an outlet of each analog switch; and

          receive the switched data at a third number of output ports, each output port capable of being coupled to a CPE device, wherein the third number is greater than

15    N.

46. A solid-state crossbar switch for transmitting DSL data traffic, comprising:

twenty-two input ports, each input port operable to receive DSL data from a data switch;

5        ninety-six output ports, each output port capable of being coupled to a CPE device; and

twenty-four 1 x 16 solid-state analog switches, each 1 x 16 solid-state analog switch operable to couple one of the input ports with sixteen output ports.

10

47. The crossbar switch of Claim 46, further comprising a sweeper port coupled to each output port, wherein the sweeper port is operable to monitor each output port to detect an active connection of a CPE  
15        device to one of the output ports.

48. The crossbar switch of Claim 46, further comprising a catcher port coupled to each output port, wherein the catcher port is operable to monitor each  
20        output port to detect an active connection of a CPE device to one of the output ports and form an active connection with one of the output ports to alleviate a bad cluster.

49. The crossbar switch of Claim 48, further comprising a sweeper port coupled to each output port, wherein the sweeper port is operable to monitor each  
25        output port to detect an active connection of a CPE device to one of the output ports.

1.0333333333333333